



OUT-4-0000

Wall Outlet allows mounting of 4xSC simplex/LC duplex

Wall outlets are used to terminate fiber optic networks on the subscriber side. They offer the possibility to install four SC simplex adapters, allowing the termination of 2 to 4 optical fibers. The simple design of the socket ensures very efficient fiber installation, and there is space inside for storing excess cable. The socket is designed for indoor installation, making it an ideal solution for various types of fiber optic installations. The subscriber indoor outlet is an excellent solution for fiber optic installations in residential and commercial buildings, providing quick and easy installation and configuration flexibility. Its simple design and the ability to mount it both on the wall and flush-mounted make it a versatile and easy-to-use product.



Technical specifications

Wall Outlet allows mounting of 4xSC simplex/LC duplex

Number of adapter slots	4 x SC simplex
Maximum number of welds	4
Cable length	cable with a diameter of 0.9 mm - 4 mb, cable with a diameter of 2 mm - 1.5 mb
IP	IP20 - IK08
Equipment	Empty (without sockets, pigtailii)
Dimensions (H/W/D)	150x110x30 [mm].
Weight	0,1kg
Color	gray (RAL7035)







Easy installation

The indoor outlet can be easily mounted thanks to its simple design. It is suitable for both wall and flush mounting, providing installation flexibility in various construction conditions.

Versatility and compatibility

The product allows the installation of four SC simplex adapters, which enables the termination of 2 to 4 optical fibers. Inside the socket, there is a removable cassette with a holder for 4 splices, which facilitates the organization and management of optical fibers.