



OUT-4-0000

Wall Outlet allows mounting of 4xSC simplex/LC duplex

Subscriber outlets are used to terminate the fiber optic network on the subscriber side. They allow for the installation of four SC simplex adapters, enabling termination of 2 to 4 optical fibers.

The simple design of the outlet ensures efficient fiber installation, with space inside for storing excess cable. The outlet is intended for indoor installation, making it an ideal solution for various types of fiber optic systems. The subscriber outlet is an excellent solution for fiber optic installations in residential and commercial buildings, ensuring quick and easy installation as well as flexibility in configuration.


Its simple design, along with the option for both surface and flush mounting, makes it a versatile and user-friendly product.



Technical specifications

Wall Outlet allows mounting of 4xSC simplex/LC duplex

Number of adapter slots	4 x SC simplex
Maximum number of welds	4
Cable length	cable with a diameter of 0.9 mm - 4 mb, cable with a diameter of 2 mm - 1.5 mb
IP	IP20 - IK08
Equipment	Empty (without sockets, pigtails)
Dimensions (H/W/D)	150x110x30 [mm].
Weight	0,1kg
Color	gray (RAL7035)



Easy installation

The subscriber outlet can be easily installed thanks to its simple design. It is suitable for both surface-mounted and flush-mounted installation, providing flexibility in various building conditions.

Versatility and compatibility

The product allows for the installation of four SC simplex adapters, enabling the termination of 2 to 4 optical fibers. Inside the outlet, there is a removable tray with holders for four splices, which makes fiber organization and management easier.